

## OSO Hotwater - ErP information

21.04.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)											
					OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Hot water 40°C [L]	Heat-up 15°C - max [Hrs]	Recovery after 75% [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]
<b>Domestic products - Direct electric</b>																
1 100 100	RM 5 - 3 kW/1x240V	Mini	200	430	0,5	7	0,15	0,11	31	593	60	6	19	C	XXS	
1 326 100	15RD 150, 3+3kW/1x240V	Slimline	430	1609	3	199	2,5	1,9	34	4978	60	143	77	E	XL	
10 801 210	SX 120 - 3 kW/1x230V	Super Xpress	580	850	2,5	190	2,8	2,1	34	1529	70	111	43	D	M	
10 801 410	SX 150 - 3+3 kW/1x230V	Super Xpress	580	1050	3	255	2,3	1,7	35	2923	70	143	53	D	L	
10 801 510	SX 180 - 3+3 kW/1x230V	Super Xpress	580	1160	3	289	2,6	1,9	35	2965	70	164	59	D	L	
10 801 610	SX 210 - 3+3 kW/1x230V	Super Xpress	580	1300	4,5	340	4,9	3,7	35	2946	70	193	65	D	L	
10 801 710	SX 250 - 3+3 kW/1x230V	Super Xpress	580	1550	4,5	425	3,7	2,8	36	4688	70	242	73	D	XL	
10 801 800	SX 300 - 3+3 kW/1x230V	Super Xpress	580	1750	6,5	497	7,2	5,4	36	4704	70	280	85	D	XL	
<b>Domestic products - Indirect</b>																
1 326 200	15 RI 150 - 2 kW/1x240V + coil 0,7m <sup>2</sup>	Slimline Coil	430	1613	3	-	1,0	0,70	-	-	-	141	81	D	-	
10 803 210	SC 120 - 3 kW/1x230V + coil 0,5m <sup>2</sup>	Super Coil	580	850	2,5	-	0,40	0,28	-	-	-	109	44	B	-	
10 803 410	SC 150 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Super Coil	580	1050	3	-	0,27	0,18	-	-	-	142	54	B	-	
10 803 510	SC 180 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Super Coil	580	1160	3	-	0,30	0,22	-	-	-	163	61	C	-	
10 803 610	SC 210 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Super Coil	580	1300	4	-	0,37	0,25	-	-	-	190	67	C	-	
10 803 710	SC 250 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Super Coil	580	1550	4,5	-	0,45	0,32	-	-	-	239	80	C	-	
10 803 800	SC 300 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Super Coil	580	1710	6	-	0,53	0,37	-	-	-	277	89	C	-	
10 201 200	DC 120 - 3 kW/1x230V + coil 0,5m <sup>2</sup>	Delta Coil	595	845	2,5	-	0,35	0,25	-	-	-	115	35	A	-	
10 201 400	DC 150 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Delta Coil	595	1005	3	-	0,40	0,30	-	-	-	145	39	A	-	
10 201 500	DC 180 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Delta Coil	595	1170	3	-	0,50	0,37	-	-	-	175	42	A	-	
10 201 600	DC 210 - 3 kW/1x230V+Coil 0,8m <sup>2</sup>	Delta Coil	595	1270	4	-	0,53	0,40	-	-	-	194	43	A	-	
10 201 700	DC 250 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Delta Coil	595	1540	4,5	-	0,72	0,53	-	-	-	245	47	A	-	
10 201 800	DC 300 - 3 kW/1x230V + coil 0,8m <sup>2</sup>	Delta Coil	595	1750	6	-	0,82	0,62	-	-	-	284	49	A	-	
10 231 700	DCF 250-3kW/1x230V+Coil 0,8m <sup>2</sup>	Delta F1 Coil	595	1540	5	-	Heat Source	Heat Source	-	-	-	245	47	A	-	
10 231 800	DCF 300-3kW/1x230V+Coil 0,8m <sup>2</sup>	Delta F1 Coil	595	1750	6	-	Heat Source	Heat Source	-	-	-	284	49	A	-	
10 221 600	DGC 200-3kW/1x230V+Coil 1,4m <sup>2</sup>	Delta Geo Coil	595	1270	4	-	Heat Source	Heat Source	-	-	-	194	43	A	-	
10 221 700	DGC 250-3kW/1x230V+Coil 1,8m <sup>2</sup>	Delta Geo Coil	595	1540	4,5	-	Heat Source	Heat Source	-	-	-	245	47	A	-	
10 221 800	DGC 300-3kW/1x230V+Coil 1,8m <sup>2</sup>	Delta Geo Coil	595	1750	6	-	Heat Source	Heat Source	-	-	-	284	49	A	-	

## OSO Hotwater - ErP information

21.04.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)										
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Hot water 40°C [L]	Heat-up 15°C - max [Hrs]	Recovery after 75% [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
10 211 600	DTC 200-3kW/1x230V+Coil 0,7m <sup>2</sup> +0,7m <sup>2</sup>	Delta Twin Coil	595	1270	4	-	Heat Source	Heat Source	-	-	-	192	49	B	-
10 211 700	DTC 250-3kW/1x230V+Coil 0,7m <sup>2</sup> +0,7m <sup>2</sup>	Delta Twin Coil	595	1540	5	-	Heat Source	Heat Source	-	-	-	242	54	B	-
10 211 800	DTC 300-3kW/1x230V+Coil 0,7m <sup>2</sup> +0,7m <sup>2</sup>	Delta Twin Coil	595	1750	6	-	Heat Source	Heat Source	-	-	-	284	58	B	-

1 327 030	RI 120, 3 kW/1x230V+0,4m <sup>2</sup>	Ecoline Coil	580	724	2,5	-	Heat Source	Heat Source	-	-	-	108	43	B	-
1 327 040	RI 150, 3 kW/1x230V+0,8m <sup>2</sup>	Ecoline Coil	580	904	3	-	Heat Source	Heat Source	-	-	-	141	51	B	-
1 327 050	RI 180, 3 kW/1x230V+0,8m <sup>2</sup>	Ecoline Coil	580	1014	3	-	Heat Source	Heat Source	-	-	-	160	58	C	-
1 327 060	RI 210, 3 kW/1x230V+0,8m <sup>2</sup>	Ecoline Coil	580	1154	4	-	Heat Source	Heat Source	-	-	-	186	62	C	-
1 327 070	RI 250, 3 kW/1x230V+0,8m <sup>2</sup>	Ecoline Coil	580	1404	4,5	-	Heat Source	Heat Source	-	-	-	233	74	C	-
1 327 080	RI 300, 3 kW/1x230V+0,8m <sup>2</sup>	Ecoline Coil	580	1604	5	-	Heat Source	Heat Source	-	-	-	271	81	C	-