

# Slimline Indirect - RI - for tight spaces



## Perfect for tight and narrow spaces

The Slimline is the slimmest domestic cylinder available at only 430 mm diameter, making the cylinder ideal for installation in tight spaces. The cylinder has a large heating coil for fast heating and also back-up electric heating from an immersion heater. Low heat loss comes from OSO ECO Foam insulation. High flow rates provide powerful showers.

The cylinder is floor mounted and is supplied with a wall bracket to stabilize the unit. An external expansion vessel is supplied with its own wall bracket.

Slimline is simple to fit and follows a similar installation technique to the OSO renewable and PowerCyl cylinders. A dedicated secondary return is supplied as standard.

Heating coils in OSO cylinders are made of smooth coil that will not encourage lime-scale deposits and offer longer and more efficient life than finned or rippled coils. OSO coils have increased length compared to finned coils, carry more heating fluid and therefore have a greater heat transfer capacity.

### ADVANTAGES

- Lightweight and compact cylinder for easy handling and installation
- Short heat-up time from large coil
- OSO ECO Foam insulation and 10 year guarantee

### PRODUCT DATA

Guarantee	Tank 10 yrs* - parts 2 yrs
Insulation	ECO Foam - water based
Certification	CE / KIWVA
El. element	1" thread
Thermostat	40-70°C (preset 60°C)
Exp. vessel	External
Safety valve	10 bar/90-95°C - fitted

\*Subject to T&C

### Technical Data Fiche

Prod. No.	Product code:	Capacity persons	Weight kg.	DiaxHeight mm.	Coil rating kW*	Recovery time min.	Volume L	Heat loss kWh/d	Heat loss W	Rating ErP
132 6200	RI 150 - 2kW/1x240V+coil 0.7m <sup>2</sup>	25	46	ø430x1610	8	42	141	1.94	81	D

\*Tested to BS EN 12897

Subject to changes without notice